

## S P E C I F I C A T I O N S

### Weight (lbs.)

<b>Max GVWR</b>	14,500
Front	5,360
Rear	9,880
<b>Body/Payload</b>	Up to 9,450*

### Dimensions (in.)

<b>Wheelbase</b>	108.3/131.9/148.0
<b>Usable cab to rear axle</b>	83.1/106.7/122.9
<b>Overall length (End of frame)</b>	192.3/215.7/231.9

### Engine

<b>Model</b>	Mitsubishi 4D34-2AT3B
<b>Type</b>	4-stroke cycle, watercooled, direct injection, turbocharged, intercooled diesel
<b>No. of cylinders</b>	Four in-line
<b>Piston displacement</b>	238.0 cu. in. (3.9 liters)
<b>Max. output (SAE, gross)</b>	145 hp/2,900 rpm
<b>Max. torque (SAE, gross)</b>	275 lb.ft./1,600 rpm
<b>Air cleaner</b>	Dry paper element with snorkel and rain cap
<b>Starter</b>	12-volt
<b>Alternator</b>	12-volt, 80-amp

### Chassis

<b>Clutch</b>	Hydraulic control, 11.8 in., single dry plate
<b>Transmission (Automatic option)</b>	5 forward and 1 reverse speed, 2nd to 5th synchromesh, 1st and reverse constant mesh gears
Ratio: manual	5.380/3.028/1.700/1.000/0.722, reverse 5.380
Ratio: automatic	3.018/1.548/1.000/0.703, reverse 2.678
<b>Axle</b>	
Front	Reverse Elliot, I-beam-type, 5,510 lbs. capacity
Rear	Full-floating-type, 10,360 lbs. capacity
<b>Final reduction gear</b>	Single-reduction hypoid gear
Ratio	5.714 (manual/automatic)
<b>Tires</b>	Single front steer, dual rear traction
Size	LT215/85R16E (10 PR)
<b>Steering</b>	Ball-nut-type with integral-type hydraulic power booster. Telescopic and tilt steering column with steering lock
<b>Suspension</b>	
Front	Super Heavy-Duty laminated leaf springs with shock absorbers and stabilizer bar
Rear	Super Heavy-Duty laminated leaf springs with shock absorbers and stabilizer bar
<b>Brakes</b>	
Service	Hydraulic with vacuum servo assist, dual-caliper four-wheel disc brakes
Parking	Internal expanding shoe-type
<b>Fuel tank</b>	33 gallons
<b>Electrical system</b>	Two 12-volt, maintenance-free batteries
<b>Cab</b>	All-steel, tilt cab

\*Weight approximate. See dealer for complete details.

FE·SP



1 9 9 9

# FE·SP


MITSUBISHI FUSO TRUCK  
OF AMERICA, Inc.  
P.O. Box 464  
100 Center Square Road  
Bridgeport, NJ 08014

For the dealer nearest you,  
or for more information, write  
or call: 1 (800) 648-3876

Or visit our web site at  
<http://www.mitfuso.com>

Vehicle specifications are subject to change  
without notice. Photos and descriptions included  
in this brochure may vary in comparison to  
actual vehicle models.

 PRINTED IN THE U.S.A. ON RECYCLED AND  
RECYCLABLE PAPER 4/98. ©1998 MITSUBISHI FUSO  
TRUCK OF AMERICA, INC.



A. Wheelbase (in.)

108.3/131.9/148.0

B. Usable cab to rear axle (in.)

83.1/106.7/122.9

C. Overall length (in.)

192.3/215.7/231.9

