

FE-SP

S P E C I F I C A T I O N S



2003

Weight (lbs.)

Max. GVWR	14,500
Front	5,360
Rear	9,880
Body/Payload	Up to 9,330*

Dimensions (in.)

Wheelbase	108.3/131.9/148.0/165.4
Usable cab to rear axle	83.1/106.7/122.9/142.3
Overall length (End of frame)	192.3/215.7/232.1/251.4

Engine

Type	4-stroke cycle, watercooled, direct injection, turbocharged, intercooled diesel	
No. of cylinders	Four in-line	
Model	Mitsubishi 4D34-3AT3B	Mitsubishi 4M50-1AT2
Piston displacement	238.0 cu. in. (3.9 liters)	299.0 cu. in. (4.9 liters)
Max. output (SAE, gross)	145 hp@2,900 rpm	175 hp@2,700 rpm
Max. torque (SAE, gross)	275 lb.ft.@1,600 rpm	347 lb.ft.@1,800 rpm
Air cleaner	Dry paper element with snorkel and rain cap	
Starter	12-volt	
Alternator	12-volt, 100-amp	


Chassis

Clutch	Hydraulic control, 11.8 in., single dry plate	
Transmission	5 forward & 1 reverse speed 2nd to 5th synchromesh, 1st & reverse constant mesh gears	4-speed automatic
Ratio	5.380/3.028/1.700/1.000/0.722, reverse 5.380	3.018/1.548/1.000/0.703, reverse 2.678
Axle	Front	Reverse Elliot, I-beam-type, 5,510 lbs. capacity
	Rear	Full-floating-type, 9,920 lbs. capacity
Final reduction gear	Single-reduction hypoid gear	
Ratio	5.714 (manual), 5.285 (automatic)	
Tires (Premium)	Single front, dual rear	
Size	LT215/85R16E (10 PR)	
Steering	Ball-nut-type with integral-type hydraulic power booster. Telescopic and tilt steering column with steering lock	
Suspension	Front	Super Heavy-duty laminated leaf springs with shock absorbers and stabilizer bar
	Rear	Super Heavy-duty laminated leaf springs with shock absorbers and stabilizer bar
Brakes	Service	Hydraulic with vacuum servo assist, ABS dual-caliper four-wheel disc brakes with exhaust brake
	Parking	Internal expanding shoe-type
Fuel tank	33 gallons	
Electrical system	Two 12-volt, maintenance-free batteries	
Vehicle safety	Energy-absorbing steering wheel, crush bars in doors, daytime running lights and ABS standard	

*Weight approximate. See dealer for complete details.

FE-SP

SPECIFICATIONS



A. Wheelbase (in.)


108.3/131.9/148.0/165.4

B. Usable cab to rear axle (in.)

83.1/106.7/122.9/142.3

C. Overall length (in.)

192.3/215.7/232.1/251.4





2003

**MITSUBISHI FUSO TRUCK
OF AMERICA, Inc.**
2015 Center Square Road
Logan Twp., NJ 08085

For the dealer nearest you,
or for more information,
call: **877-202-9650**

Or visit our web site at:
www.mitfuso.com



Vehicle specifications are subject to change
without notice. Photos and descriptions included
on this spec sheet may vary in comparison to
actual vehicle models.

PRINTED IN THE U.S.A. ON RECYCLED AND
RECYCLABLE PAPER 6/02. ©2002 MITSUBISHI FUSO
TRUCK OF AMERICA, Inc.

MKT0304